

Erklärung

Sehr geehrte Kunden,


Hiermit bestätigt die WKK GmbH, dass Schrumpfschläuche nach UL YDPU2 gelistet sind.
Für weitere Informationen und Ausnahmen siehe Anlage.

Bram Boers

Geschäftsführer | E: bram.boers@wkk-deutschland.de

T: 02157/1389-24 | F: 02157/1389-97

März 2022

WKK GmbH

WKK GmbH
Zillessen-Allee 7
D-41334 Nettetal-Kaldenkirchen
Tel.: 02157 - 1389-0
Fax: 02157 - 1389-99



YDPU2.E204071
Tubing, Extruded Insulating - Component

Page Bottom

Tubing, Extruded Insulating - Component

See General Information for Tubing, Extruded Insulating - Component

HONGSHANG HEAT SHRINKABLE MATERIALS CO LTD

E204071

No.8 Jinlong Rd

Baolong Industrial Area, Longgang

Shenzhen, Guangdong 518000 CHINA

Cat. No.	Max V rms	Max Oper Temp, °C	Color Recognized	Oil-resistance Class[a]	VW-1 Rated[b]
Flexible heat shrinkable Polyolefin tubing					
H-2(CB)	300	125	BK	None	Yes
Flexible (Layflat) heat shrinkable Polyolefin tubing					
H-2(Z) 2PF (a)	600	125	All except clear	None	Yes
Flexible heat shrinkable Polyolefin tubing					
H-2(Z), H-2(3X)	600	125	All except clear	None	Yes
H-2(ZH)(3X), H-2(HF)(3X)	600	125	All except clear	None	Yes
H-2(ZH), H-2(HF)	600	125	All except clear	None	Yes
Flexible (Layflat) heat shrinkable Polyolefin tubing					
H-2F 2PF (a), H-2F 3PF (a)	600	125	All except clear	None	Yes
Flexible heat shrinkable Polyolefin tubing					
H-2F(X), H-2F(2X), H-2F(3X), H-2F(4X), H-2R, H-100	600	125	All except clear	None	Yes
Flexible (Layflat) heat shrinkable Polyolefin tubing					
H-2R 2PF (a), H-2R 3PF (a)	600	125	All except clear	None	Yes
Heat shrinkable Polyolefin tubing with meltable adhesive liner					
H-5(2X), H-5(3X), H-5(4X)	600	125	BK	None	Yes
H-5(2X)F, H-5(3X)F, H-5(4X)F	600	125	BK	None	Yes

[a] - Tubing is considered to comply with the optional Oil Resistance requirements only if authorized in the above table and marked "Oil Resistant" (or "Oil Res"), followed by the class (01, 02 or 03).

[b] - Tubing is considered to comply with the optional VW-1 flammability requirements only if authorized in the above table and if so marked.

(a) - For the suffix PF: P indicates printable (not evaluated) and F indicates provided flat. The number before the PF indicates the expansion ratio.

Marking: Company name or tradename "E204071" , catalog designation, inside diameter (before and after recovery for heat-shrinkable tubing), voltage rating, temperature rating in degrees Celsius and date of manufacture (or traceable code) printed on tags attached to both ends of the tubing or printed on the shipping spool label or smallest unit container in which the product is packaged.

Last Updated on 2016-08-19

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".